

NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

SECTION 1. IDENTIFICATION

Product name : NeXtal ComPAS Suite

Manufacturer or supplier's details

Company : NeXtal

6201 Trust Dr Holland, OH 43528

USA

Telephone : 419-740-6600

E-mail address : www.calibrescientific.com

Emergency telephone : CHEMTREC

USA & Canada 1-800-424-9300

Outside USA & Canada (703) 527-3887

Chemtrec ID# 696910

Recommended use of the chemical and restrictions on use

Recommended use : Laboratory chemicals

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 1A

Reproductive toxicity : Category 1B



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Specific target organ systemic toxicity - single

exposure

: Category 1

Specific target organ systemic toxicity - single

exposure

: Category 3 (Respiratory system, Central nervous system)

Specific target organ

systemic toxicity - repeated

exposure

: Category 2

GHS Label element

Hazard pictograms









Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H302 + H312 Harmful if swallowed or in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or

repeated exposure.

Precautionary Statements

: Prevention:

P201 Obtain special instructions before use.

P210 Keep away from heat/sparks/open flames/hot surfaces.

P260 Do not breathe dust/fumes/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/

face protection.

P284 Wear respiratory protection.

Response:

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P309 + P311 IF exposed or if you feel unwell: Call a POISON

CENTER or doctor/ physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Substance name : Semifinished ComPAS

Hazardous ingredients

| Chemical Name | CAS-No. | Concentration (% w/w) |
|--|-------------|-----------------------|
| 2-methylpentane-2,4-diol | 107-41-5 | >= 70 - < 90 |
| ethanol | 64-17-5 | >= 50 - < 70 |
| 2-methylpropan-2-ol | 75-65-0 | >= 30 - < 50 |
| Magnesium chloride, hexahydrate | 7791-18-6 | >= 30 - < 50 |
| 2-propanol | 67-63-0 | >= 30 - < 50 |
| PEG | 25322-68-3 | >= 20 - < 30 |
| glycerol | 56-81-5 | >= 20 - < 30 |
| methanol | 67-56-1 | >= 20 - < 30 |
| lithium sulfate, monohydrate | 10102-25-7 | >= 10 - < 20 |
| ammonium formate | 540-69-2 | >= 10 - < 20 |
| calcium acetate hydrate | 114460-21-8 | >= 1 - < 10 |
| calcium chloride dihydrate | 10035-04-8 | >= 1 - < 10 |
| 4-Morpholineethanesulfonic acid | 145224-94-8 | >= 1 - < 10 |
| 2-(Cyclohexylamino)ethanesulfonic acid | 103-47-9 | >= 1 - < 10 |
| imidazole | 288-32-4 | >= 0.1 - < 1 |
| nickel chloride | 7791-20-0 | >= 0.1 - < 1 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

If inhaled : Call a physician or poison control center immediately.

If unconscious place in recovery position and seek medical

advice.

Keep respiratory tract clear.

In case of skin contact : Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eyes.

Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician.

If swallowed : If accidentally swallowed obtain immediate medical attention.



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Rinse mouth with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Harmful if swallowed or in contact with skin.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic if inhaled.

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : No information available.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Exposure to decomposition products may be a hazard to

health.

Hazardous combustion

products

: Carbon oxides

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).
Nitrogen oxides (NOx)
potassium oxide
Chlorine compounds
Magnesium oxides
Sulfur oxides
Metal oxides

Hydrogen chloride gas

Specific extinguishing

methods

: In the event of fire and/or explosion do not breathe fumes.

Use a water spray to cool fully closed containers.

Special protective equipment

for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

: Use personal protective equipment.

Ensure adequate ventilation.



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Remove all sources of ignition. emergency procedures

Evacuate personnel to safe areas.

Avoid breathing dust/fumes/gas/mist/vapors/spray. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

Methods and materials for

containment and cleaning up

: Contain spillage and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

: Avoid formation of aerosol. Advice on safe handling

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Materials to avoid : Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Ingredients | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--------------------------|----------|-------------------------------------|--|-----------|
| 2-methylpentane-2,4-diol | 107-41-5 | С | 25 ppm | ACGIH |
| | | С | 25 ppm 125 mg/m3 | NIOSH REL |
| | | С | 25 ppm | OSHA P0 |



NeXtal ComPAS Suite

 Version 2.0
 Revision Date 03/31/2020
 Print Date 03/31/2020

| | I | 1 | 125 mg/m3 | 1 |
|---------------------|------------|---------------------------------|--------------------------|-----------|
| ethanol | 64-17-5 | TWA | 1,000 ppm 1,900 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,900 mg/m3 | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,900 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm | ACGIH |
| 2-methylpropan-2-ol | 75-65-0 | TWA | 100 ppm | ACGIH |
| | | TWA | 100 ppm 300 mg/m3 | NIOSH REL |
| | | ST | 150 ppm 450 mg/m3 | NIOSH REL |
| | | TWA | 100 ppm 300 mg/m3 | OSHA Z-1 |
| | | TWA | 100 ppm 300 mg/m3 | OSHA P0 |
| | | STEL | 150 ppm 450 mg/m3 | OSHA P0 |
| 2-propanol | 67-63-0 | TWA | 200 ppm | ACGIH |
| | | STEL | 400 ppm | ACGIH |
| | | TWA | 400 ppm 980 mg/m3 | NIOSH REL |
| | | ST | 500 ppm 1,225 mg/m3 | NIOSH REL |
| | | TWA | 400 ppm 980 mg/m3 | OSHA Z-1 |
| | | TWA | 400 ppm 980 mg/m3 | OSHA P0 |
| | | STEL | 500 ppm 1,225 mg/m3 | OSHA P0 |
| PEG | 25322-68-3 | TWA | 10 mg/m3 | US WEEL |
| | | TWA (aerosol) | 10 mg/m3 | US WEEL |
| glycerol | 56-81-5 | TWA (mist, respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (mist, total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (Total) | 10 mg/m3 | OSHA P0 |
| | | TWA (Respirable fraction) | 5 mg/m3 | OSHA P0 |
| | | TWA | 10 mg/m3 | ACGIH |
| | | TWA (Mist - | 10 mg/m3 | OSHA P0 |
| | | total dust) | 3 3 3 | |
| | | TWA (Mist - respirable | 5 mg/m3 | OSHA P0 |
| methanol | 67-56-1 | fraction) TWA | 200 ppm | ACGIH |
| methanoi | 07-30-1 | STEL | 250 ppm | ACGIH |
| | | TWA | 200 ppm 260 mg/m3 | NIOSH REL |
| | | ST | 250 ppm | NIOSH REL |



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

| | | | 325 mg/m3 | |
|-----------------|-----------|--------------------------------|-------------------------|-----------|
| | | TWA | 200 ppm 260 mg/m3 | OSHA Z-1 |
| | | STEL | 250 ppm 325 mg/m3 | OSHA P0 |
| | | TWA | 200 ppm 260 mg/m3 | OSHA P0 |
| nickel chloride | 7791-20-0 | TWA | 1 mg/m3 (Nickel) | OSHA Z-1 |
| | | TWA (Inhalable fraction) | 0.1 mg/m3 (Nickel) | ACGIH |
| | | TWA | 0.1 mg/m3 (Nickel) | OSHA P0 |
| | | TWA | 0.015 mg/m3 (Nickel) | NIOSH REL |
| | | TWA | 1 mg/m3 (Nickel) | OSHA Z-1 |
| | | TWA (Inhalable fraction) | 0.1 mg/m3 (Nickel) | ACGIH |
| | | TWA | 0.1 mg/m3 (Nickel) | OSHA P0 |
| | | TWA | 0.015 mg/m3 (Nickel) | NIOSH REL |

Hazardous components without workplace control parameters

| Ingredients | CAS-No. |
|--|-------------|
| Magnesium chloride, | 7791-18-6 |
| hexahydrate | |
| lithium sulfate, monohydrate | 10102-25-7 |
| ammonium formate | 540-69-2 |
| calcium acetate hydrate | 114460-21-8 |
| calcium chloride dihydrate | 10035-04-8 |
| 4-Morpholineethanesulfonic acid | 145224-94-8 |
| 2-(Cyclohexylamino)ethanesulfonic acid | 103-47-9 |
| imidazole | 288-32-4 |

Biological occupational exposure limits

| Ingredients | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-------------|---------|--------------------|---------------------|--|---------------------------|--------------|
| | 67-63-0 | Acetone | Urine | End of shift at end of workweek | 40 mg/l | ACGIH BEI |
| | 67-56-1 | Methanol | Urine | End of shift (As soon as possible After exposure ceases) | 15 mg/l | ACGIH BEI |



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Personal protective equipment

Respiratory protection : In the case of vapor formation use a respirator with an

approved filter.

Hand protection

Material : Protective gloves

Remarks : The choice of an appropriate glove does not only depend on

its material but also on other quality features and is different from one producer to the other. Take note of the information given by the producer concerning permeability and break

through times, and of special workplace conditions

(mechanical strain, duration of contact).

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Do not wear contact lenses.

Ensure that eyewash stations and safety showers are close

to the workstation location.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the workplace.

Footwear protecting against chemicals Workers should wear antistatic footwear.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Keep away from food and drink.

Wash hands before breaks and immediately after handling

the product.

Ensure adequate ventilation, especially in confined areas.

Keep working clothes separately.

Avoid contact with the skin and the eyes. When using do not eat, drink or smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : No data available

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Flash point : No data available

Evaporation rate : No data available

Burning rate : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Hazardous decomposition products formed under fire

conditions.

Vapors may form explosive mixture with air.

Keep away from oxidizing agents, and acidic or alkaline

products.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or in contact with skin.

Toxic if inhaled.

Product:

Acute oral toxicity : No data available

Acute toxicity estimate: 353.74 mg/kg

Method: Calculation method

Acute inhalation toxicity : No data available

Acute toxicity estimate: 9.65 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : No data available

Acute toxicity estimate: 1,140 mg/kg

Method: Calculation method

Ingredients:

2-methylpentane-2,4-diol:

Acute oral toxicity : LD50 Oral (Rat): 3,700 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 7,892 mg/kg

ethanol:

Acute oral toxicity : LD50 Oral (Rat): 10,470 mg/kg

Acute inhalation toxicity : LC50 (Rat): 20000 ppm

Exposure time: 10 h

2-methylpropan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 2,743 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Magnesium chloride, hexahydrate:

Acute oral toxicity : LD50 Oral (Rat): 8,100 mg/kg

2-propanol:

Acute oral toxicity : LD50 Oral (Rat): 5,045 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 12,800 mg/kg

PEG:

Acute inhalation toxicity : No data available



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Acute dermal toxicity : No data available

glycerol:

Acute oral toxicity : LD50 Oral (Rat): 12,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 10,000 mg/kg

methanol:

Acute oral toxicity : LD50 Oral (Rat): 1,187 mg/kg

Acute inhalation toxicity : LC50 (Rat): 128.2 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal (Rabbit): 17,100 mg/kg

lithium sulfate, monohydrate:

Acute oral toxicity : LD50 Oral (Rat): 613 mg/kg

ammonium formate:

Acute oral toxicity : LD50 Oral (Mouse): 2,250 mg/kg

calcium acetate hydrate:

Acute oral toxicity : LD50 Oral (Rat): 4,280 mg/kg

imidazole:

Acute oral toxicity : LD50 Oral (Rat): 970 mg/kg

nickel chloride:

Acute oral toxicity : LD50 Oral (Rat): 105 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks:

May cause skin irritation and/or dermatitis.

Ingredients:

2-propanol:

Species: Rabbit

Result: Mild skin irritation

glycerol:

Species: Rabbit Exposure time: 24 h Result: Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks:

May cause irreversible eye damage.

Ingredients:



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

ethanol:

Result: Eye irritation

2-propanol:

Species: Rabbit Result: Eye irritation Exposure time: 24 h

glycerol:

Species: Rabbit

Result: Mild eye irritation Exposure time: 24 h

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

Product:

Remarks:

Causes sensitization. May cause sensitization by inhalation and skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

IARC Group 1: Carcinogenic to humans

Nickel chloride 7791-20-0

OSHANo ingredient of this product present at levels greater than

or equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP Known to be human carcinogen

Nickel chloride 7791-20-0

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs.

Ingredients:

2-propanol:

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks:

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : No data available

Toxicity to algae : No data available

Toxicity to bacteria : No data available

: LC50 (Pimephales promelas (fathead minnow)): 10,700 mg/l

Ingredients:

2-methylpentane-2,4-diol:

Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 3,200 mg/l

Exposure time: 48 h

2-methylpropan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 6,140 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 933 mg/l

Exposure time: 48 h

2-propanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l

Exposure time: 96 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (Scenedesmus

subspicatus)): 2,000 mg/l Exposure time: 72 h

PEG:

Toxicity to fish : (Leuciscus idus (Golden orfe)): > 500 mg/l

Exposure time: 96 h Test Type: static test

glycerol:

Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): > 250 mg/l

Exposure time: 48 h

methanol:



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia): 341.5 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): 133

mg/l

Exposure time: 72 h

Test Type: Growth inhibition

imidazole:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 283.6 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 341.5 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Scenedesmus quadricauda (Green algae)): 133 mg/l

Exposure time: 72 h Test Type: static test

Toxicity to bacteria : 45 mg/l

Exposure time: 0.5 h

nickel chloride:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 0.51 mg/l

Exposure time: 48 h

Persistence and degradability

Ingredients:

methanol:

Biodegradability : aerobic

Result: rapidly biodegradable

Biodegradation: 72 % Exposure time: 5 Tage

Bioaccumulative potential

Product:

Bioaccumulation : No data available

Ingredients:

methanol:

Partition coefficient: n-

octanol/water

: log Pow: -0.77

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Dispose of as unused product.

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

IATA-DGR

UN/ID No. : UN 1992

Proper shipping name : Flammable liquid, toxic, n.o.s.

(ethanol, methanol)

Class : 3
Subsidiary risk : 6.1
Packing group : II

Labels : Flammable Liquids, Toxic

IMDG-Code

UN number : UN 1992

Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.

(ethanol, methanol)

Class : 3
Subsidiary risk : 6.1
Packing group : II
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1992

Proper shipping name : FLAMMABLE LIQUIDS, TOXIC, N.O.S.

(ethanol, methanol)

Class : 3



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

Subsidiary risk : 6.1 Packing group : II

Labels : Class 3 - Flammable Liquid, Class 6 - Toxic Substance

(Division 6.1)

ERG Code : 131 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-methylpropan-2-ol 75-65-0

methanol 67-56-1

nickel chloride 7791-20-0

US State Regulations

California Prop. 65 WARNING! This product contains a chemical known in the

State of California to cause cancer.

ethanol 64-17-5 nickel chloride 7791-20-0

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive

harm.

ethanol 64-17-5 methanol 67-56-1

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations



NeXtal ComPAS Suite

Version 2.0 Revision Date 03/31/2020 Print Date 03/31/2020

(Q)SAR - (Quantitative) Structure Activity Relationship; ASTM - American Society for the Testing of Materials: bw - Body weight: DIN - Standard of the German Institute for Standardisation: ECx -Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative; DSL -Domestic Substances List (Canada); KECI - Korea Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); AICS - Australian Inventory of Chemical Substances; IECSC - Inventory of Existing Chemical Substances in China; ENCS - Existing and New Chemical Substances (Japan): ISHL - Industrial Safety and Health Law (Japan): PICCS - Philippines Inventory of Chemicals and Chemical Substances: NZIoC - New Zealand Inventory of Chemicals: TCSI - Taiwan Chemical Substance Inventory: CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; DOT - Department of Transportation; EHS -Extremely Hazardous Substance; HMIS - Hazardous Materials Identification System; MSHA -Mine Safety and Health Administration; NFPA - National Fire Protection Association; RCRA -Resource Conservation and Recovery Act; RQ - Reportable Quantity; SARA - Superfund Amendments and Reauthorization Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; GLP - Good Laboratory Practice; ERG - Emergency Response Guide; NTP - National Toxicology Program; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods

Revision Date : 03/31/2020

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.